

Kanalna jedinica

- Najmanja visina ugradnje od samo 210 mm
- Podesivi vanjski statički tlak do 45Pa
- Uključena pumpa za odvod kondenzata



UNUTARNJA JEDINICA		RAS-M10U2DVG-E	RAS-M13U2DVG-E	RAS-M16U2DVG-E	RAS-M22U2DVG-E	RAS-M24U2DVG-E
Učin hlađenja	kW ❄️	2,70	3,70	4,50	6,00	7,00
Razina zvučnog tlaka (niska/srednja/visoka)	dB(A) ❄️	27/35	27/37	24/35	32/38	33/39
Učin grijanja	kW 🔥	4,00	5,00	5,50	7,00	8,00
Razina zvučnog tlaka (niska/srednja/visoka)	dB(A) 🔥	27/35	27/37	25/35	32/38	33/39
Protok zraka	m³/h	570	610	780	1000	1060
Vanjski statički tlak	Pa	10/20/35/45	10/20/35/45	10/20/35/45	10/20/35/45	10/20/35/45
Dimenzije (VxŠxD)	mm	210 x 700 x 450	210 x 700 x 450	210 x 900 x 450	210 x 1100 x 450	210 x 1100 x 450
Težina	kg	16	16	19	22	22
Cijena	kn	4.664,-	4.842,-	5.177,-	6.025,-	6.114,-

PRIBOR	OPIS	UKLJUČENO	CIJENA KN
Daljinski upravljač	Priložen je infracrveni daljinski upravljač	✓	
RB-RWS21-E	Žičani daljinski upravljač s tjednim vremenskim programatorom		1.232,-

Sve opcionalne mogućnosti za upravljanje možete pronaći od stranice 20.

